

# C-Line Magnetic Locks

## Entry level

CDVI Group Products

### Range: Electromagnetic Locks

The C-Line range of electromagnetic locks have been designed to provide a high performance, cost-effective solution to the competitive end of the magnetic locking market.

The range includes mortice and surface magnets, single and double, and 300kg or 500kg holding force (see below tables for details).

All the magnetic locks supplied in this range are monitored as standard, with a bi-coloured LED (surface models only) for visual verification of lock status and changeover relay for use if remote monitoring is required - with the focus on cost and performance, this range is certainly within the "more for less" category.

For monitoring of the door position, simply add the DPM 300 or 500.

Each model is supplied with the magnet, armature plate, template, fitting instructions and fixing kit.

All the magnets within the C-Line range are fully compatible with the brackets, housings and accessories manufactured by CDVI. A standard warranty of 12 months applies to the range.



### Technical specification

Voltage:	12 or 24Vdc
Current:	610mA @ 12Vdc 305mA @ 24Vdc
Monitoring:	Changeover (COM/NO/NC)
Indication:	Bi-colour LED (surface only)
Dimensions:	(l x w x d)
C3M11	228 x 38 x 27mm
C3S11	255 x 45 x 26mm
C3S12	504 x 45 x 26mm
C5S11	275 x 65 x 40mm
C5S12	542 x 65 x 40mm

### Product codes

<b>C3M11</b>	Mortice magnet, monitored, 300kg
<b>C3S11</b>	Surface magnet, monitored, 300kg
<b>C3S12</b>	Surface double magnet, monitored, 300kg
<b>C5S11</b>	Surface magnet, monitored, 500kg
<b>C5S12</b>	Surface double magnet, monitored, 500kg
<b>DPM300</b>	Door position monitor for 300kg surface mags
<b>DPM500</b>	Door position monitor for 500kg surface mags